

SATELITE/PRO

ES





Montaje: Empotrable.
Fuente de luz: Módulos SMD.
 Temperatura de color seleccionable CCT: 3000K, 4000K, 6000K.
Sistema óptico: Difusor opal.
Distribución luminosa: Directa.
Equipo eléctrico: Equipo de control electrónico. PF>0,95. Disponible, regulación 1-10V o DALI y/o kit de emergencia (1-3h).
Materiales: Cuerpo: Aluminio extruido lacado en blanco. Difusor: Opal.
Acabado: Color blanco RAL 9003.


EN




Mounting: Recessed.
Light source: SMD modules.
 Selectable temperature color CCT: 3000K, 4000K, 6000K.
Optical system: Opal diffuser.
Light distribution: Direct.
Electrical equipment: Electronic control gear. PF>0,95. Available, dimmable electronic control gear 1-10V or DALI and/or emergency kit (1-3h).
Materials: Body: Aluminum extruded lacquered in white. Diffuser: Opal.
Surface finish: White RAL 9003.




SATELITE/PRO-90




SATELITE/PRO-120



SATELITE/PRO-145



SATELITE/PRO-175



SATELITE/PRO-220

ESTANDAR/STANDARD

5 AÑOS / 5 YEARS
 220-240V / 50-60Hz
 IP 44
 IK 07
 CLASE II / CLASS II
 50.000h / L80B10
 -20° / +35°
 CRI 80
 3000K / 4000K / 6000K

DISPONIBLE/AVAILABLE

EMERGENCY
 1-10V / DALI
 1h / 3h

CONFIGURACION ONLINE / ONLINE CONFIGURATION



Código / Code	Referencia / Reference	Kg / Kg	Potencia / Power	Lúmenes / Lumens	Eficiencia / Efficiency	CCT (K) / CCT (K)
DS40C880B	SATELITE/PRO-90-8W 880lm/830-840-860	0,10	8W	880	110 lm/W	3000, 4000, 6000
DS40C1K1B	SATELITE/PRO-90-10W 1100lm/830-840-860	0,10	10W	1100	110 lm/W	3000, 4000, 6000
DS41C1K1B	SATELITE/PRO-120-10W 1100lm/830-840-860	0,125	10W	1100	110 lm/W	3000, 4000, 6000
DS41C1K3B	SATELITE/PRO-120-12W 1320lm/830-840-860	0,125	12W	1320	110 lm/W	3000, 4000, 6000
DS42C1K3B	SATELITE/PRO-145-12W 1320lm/830-840-860	0,160	12W	1320	110 lm/W	3000, 4000, 6000
DS42C1K9B	SATELITE/PRO-145-18W 1980lm/830-840-860	0,160	18W	1980	110 lm/W	3000, 4000, 6000
DS43C1K3B	SATELITE/PRO-175-12W 1320lm/830-840-860	0,225	12W	1320	110 lm/W	3000, 4000, 6000
DS43C1K9B	SATELITE/PRO-175-18W 1980lm/830-840-860	0,225	18W	1980	110 lm/W	3000, 4000, 6000
DS43C2K6B	SATELITE/PRO-175-24W 2640lm/830-840-860	0,225	24W	2640	110 lm/W	3000, 4000, 6000
DS44C1K3B	SATELITE/PRO-220-12W 1320lm/830-840-860	0,330	12W	1320	110 lm/W	3000, 4000, 6000
DS44C1K9B	SATELITE/PRO-220-18W 1980lm/830-840-860	0,330	18W	1980	110 lm/W	3000, 4000, 6000
DS44C2K6B	SATELITE/PRO-220-24W 2640lm/830-840-860	0,330	24W	2640	110 lm/W	3000, 4000, 6000
DS44C3K9B	SATELITE/PRO-220-36W 3960lm/830-840-860	0,330	36W	3960	110 lm/W	3000, 4000, 6000

ACCESORIOS DISPONIBLES/AVAILABLE ACCESSORIES

REGULACION/DIMMING 1-10V | DALI KIT DE EMERGENCIA/EMERGENCY KIT 1h | 3h ARO PARA TECHO DE ESCAYOLA/FRAME FOR PLASTER CEILING