

Spheric Polycarbonate Luminaires against lighting pollution



LUMINAIRE BASE: Die-cast aluminium (A) or polycarbonate (P), unbreakable and stable, in semi-spheric shape for perfect fitting to diffusers with joining handle for Ø 50 or 60 mm columns.

PAINTING: In grey epoxy-polyester RAL 7035 in robotic cabin and dust polymerization in ovens at constant temperatures of 180°. Stable to weather conditions and yellowing process.

DIFFUSERS: Spheric stable polycarbonate diffusers, prismatic or colourless with a cover painting in grey or black colour. Excellent flux transmission and proper glare reduction quality. Also available anti-glare reflector (laminar reflector Ref. LR) and embellishment cover box for covering the electrical equipment (Ref. CB) to be incorporated to luminaire.

REGULATIONS: In accordance with EEC regulations, EN-60598, Low Voltage Directive (LV) 73/23/EEC, as well as Electromagnetic Compatibility (EMC) 89/336/EEC.



LPP-I/APL/Grey-500

- LPP-I/APL-500 (VM-80 W.)
- LPP-I/APL-500 (VM-125 W.)
- LPP-I/APL-500 (HPS-70 W.)
- LPP-I/APL-500 (HPS-100 W.)
- LPP-I/APL-500 (HPS-150 W.)
- LPP-I/APL-500 (VM-250 W.)



LPI/APL/Black-500

