

# T55



## Recessed Low Luminance Luminaires for T-5 Lamp



**LUMINAIRE HOUSING:** Made in white, stoved steel sheet with high torsion resistance and a minimum guaranteed thickness of 0,6 mm according to Norm ENEC-10/VDE. Minted, punched and folded before the painting treatment.

**PAINTING:** In white epoxi-polyester, in robotic cabin with dust polymerization in continuous ovens at 180°, previous to degreasing and microcrystalline phosphatizing. Stable to the ultraviolet radiations and yellowing process. T-8 chassis with T-5 accesories.

**ACCESSORIES:** Brackets for plaster ceilings, under request.

### T55/UM

**OPTIC:** Parabolic high bright louvre, cat II, with perimetral finish decorative frame for embellishment. Anodized and polished aluminium, glare free.

Louvre cross blades (transversals) in semi-bright, flat plates in white microperforated.

	Dimensions	Ceiling Module	Hole Ceiling
<b>T55/UM - 4X28W H.F.</b>	1.195x595	1.200x600	1.175x575
<b>T55/UM - 3X28W H.F.</b>	1.195x595	1.200x600	1.175x575
<b>T55/UM - 4X24W H.F.</b>	595x595	600x600	575x575
<b>T55/UM - 3X24W H.F.</b>	595x595	600x600	575x575
<b>T55/UM - 4X14W H.F.</b>	595x595	600x600	575x575
<b>T55/UM - 3X14W H.F.</b>	595x595	600x600	575x575
<b>T55/UM - 2X28W H.F.</b>	1.195x295	1.200x300	1.175x275



### T55/UMM

**OPTIC:** Parabolic mat-satinated louvre, cat II, with perimetral finish decorative frame for embellishment. Anodized and polished aluminium, glare free.

Cross blades (transversals) in semi-mat, flat plates in white microperforated.



	Dimensions	Ceiling Module	Hole Ceiling
<b>T55/UMM - 4X28W H.F.</b>	1.195x595	1.200x600	1.175x575
<b>T55/UMM - 3X28W H.F.</b>	1.195x595	1.200x600	1.175x575
<b>T55/UMM - 4X24W H.F.</b>	595x595	600x600	575x575
<b>T55/UMM - 3X24W H.F.</b>	595x595	600x600	575x575
<b>T55/UMM - 4X14W H.F.</b>	595x595	600x600	575x575
<b>T55/UMM - 3X14W H.F.</b>	595x595	600x600	575x575
<b>T55/UMM - 2X28W H.F.</b>	1.195x295	1.200x300	1.175x275

**T55/UM 4x14 W.**

