


Recessed Low Luminance Luminaires for T-5 Lamp



LUMINAIRE HOUSING: Made in white, stoved steel sheet with high torsion resistance and a minimum guaranteed thickness of 0,6 mm according to Norm ENEC-10/VDE. Minted, punched and folded before the painting treatment.

PAINTING: In white epoxi-polyester, in robotic cabin with dust polymerization in continuous ovens at 180°, previous to degreasing and microcrystalline phosphatizing. Stable to the ultraviolet radiations and yellowing process.



T5/PRISMA

OPTIC: Made of pure methacrylate (PMMA) prismatic plate. Mounted in a steel frame coated with powder, thermo-hardened in UV stabilised and remains "CRYSTAL CLEAR" during its service life. Four metal springs are included for hanging the frame-prismatic plate for easy tubes replacement and maintenance.



EXPOSED T MODULAR CEILINGS	
DIMENSIONS	
T5/PRISMA - 4X14W H.F.	595x595x60
T5/PRISMA - 4X24W H.F.	595x595x60
T5/PRISMA - 2X28W H.F.	1.195x295x60
T5/PRISMA - 2X54W H.F.	1.195x295x60

T5/OPAL

OPTIC: Made of pure methacrylate (PMMA) opal plate. Mounted in a steel frame coated with powder, thermohardened in UV stabilised and has remains anti-yellowing process. Four metal springs are included for hanging the frame-opal plate for easy tubes replacement and maintenance.



EXPOSED T MODULAR CEILINGS	
DIMENSIONS	
T5/OPAL - 4X14W H.F.	595x595x60
T5/OPAL - 4X24W H.F.	595x595x60
T5/OPAL - 2X28W H.F.	1.195x295x60
T5/OPAL - 2X54W H.F.	1.195x295x60