






SURFACE T5 IP44 • H.F.

SURFACE T5
OPTIMA/OPAL
OPTIMA/PRISMA




OPTIMA/OPAL




Mounting	Surface.
Lamps	T5
Optical system	Opal/prism diffuser.
Light distribution	Direct.
Wiring	Electronic control gear (EEI=A2). PF>0,95 Possibility of incorporating dimmable electronic control gear (EEI=A1 1-10V or DALI) and/or emergency Kit (1 or 3 hours).
Material	Body: Steel. Diffuser: Opal or prismatic polycarbonate.
Surface finish	White.

Mounting



	L	S
1x14 / 1x24 / 2x14W.	594	380
1x28 / 1x54 / 2x28W.	1194	1000
1x35 / 1x49 / 2x35 / 2x49W.	1494	1300



AVAILABLE



CODE	REFERENCE	Kg.	Power	Lamp	Lampholder	DIMM		Emergency	
						1-10V	DALI	MC-1	MC-3
			W						
030243114	OPTIMA/OPAL-1x14W H.F.	(2,0)	14	T5	G5	✓	✓	✓	✓
030243124	OPTIMA/OPAL-1x24W H.F.	(2,0)	24	T5	G5	✓	✓	✓	✓
030243128	OPTIMA/OPAL-1x28W H.F.	(3,4)	28	T5	G5	✓	✓	✓	✓
030243154	OPTIMA/OPAL-1x54W H.F.	(3,4)	54	T5	G5	✓	✓	✓	✓
030243135	OPTIMA/OPAL-1x35W H.F.	(4,2)	35	T5	G5	✓	✓	✓	✓
030243149	OPTIMA/OPAL-1x49W H.F.	(4,2)	49	T5	G5	✓	✓	✓	✓
030243214	OPTIMA/OPAL-2x14W H.F.	(2,0)	28	T5	G5	✓	✓	✓	✓
030243228	OPTIMA/OPAL-2x28W H.F.	(3,4)	56	T5	G5	✓	✓	✓	✓
030243235	OPTIMA/OPAL-2x35W H.F.	(4,2)	70	T5	G5	✓	✓	✓	✓
030243249	OPTIMA/OPAL-2x49W H.F.	(4,2)	98	T5	G5	✓	✓	✓	✓
030253114	OPTIMA/PRISMA-1x14W H.F.	(2,0)	14	T5	G5	✓	✓	✓	✓
030253124	OPTIMA/PRISMA-1x24W H.F.	(2,0)	24	T5	G5	✓	✓	✓	✓
030253128	OPTIMA/PRISMA-1x28W H.F.	(3,4)	28	T5	G5	✓	✓	✓	✓
030253154	OPTIMA/PRISMA-1x54W H.F.	(3,4)	54	T5	G5	✓	✓	✓	✓
030253135	OPTIMA/PRISMA-1x35W H.F.	(4,2)	35	T5	G5	✓	✓	✓	✓
030253149	OPTIMA/PRISMA-1x49W H.F.	(4,2)	49	T5	G5	✓	✓	✓	✓
030253214	OPTIMA/PRISMA-2x14W H.F.	(2,0)	28	T5	G5	✓	✓	✓	✓
030253228	OPTIMA/PRISMA-2x28W H.F.	(3,4)	56	T5	G5	✓	✓	✓	✓
030253235	OPTIMA/PRISMA-2x35W H.F.	(4,2)	70	T5	G5	✓	✓	✓	✓
030253249	OPTIMA/PRISMA-2x49W H.F.	(4,2)	98	T5	G5	✓	✓	✓	✓
15620001	SUSPENSION SET 4 UNITS	-	-	-	-	-	-	-	-