




# RECESSED INDIRECT • LED

## POLYVALENT



RECESSED INDIRECT LED  
MICROPERFORATED  
LD-LED/C



LD-LED/C

|                           |   |
|---------------------------|---|
| <b>Mounting</b>           | Recessed. Armstrong ceilings, plaster, plasterboard.  |
| <b>Light source</b>       | LED  OSRAM/TRIDONIC. Colour temperature 4000K. Under request, 3000K.  |
| <b>Optical system</b>     | Diffuser.   |
| <b>Light distribution</b> | Indirect.   |
| <b>Wiring</b>             | Electronic control gear (EEI=A+). PF>0,95 OSRAM/TRIDONIC/HELVAR.<br>Possibility of incorporating dimmable electronic control gear (DALI) and/or emergency Kit (1 or 3 hours).   |
| <b>Material</b>           | Body: White enameled steel. High torsional strength and guaranteed minimum thickness of 0.6mm, according to ENEC-10 and VDE standards.<br>Diffuser: Microperforated.<br>Simple assembly and easy installation, for its quick accessibility to the connection terminal.  |
| <b>Surface finish</b>     | Body: Epoxy-polyester in white opaque and satin antiglare.<br>Stable to ultraviolet and anti-yellowing radiations.  |
| <b>Benefits</b>           | LED luminaire with integrated electronic control gear.<br>Technological guarantee.<br>Optimal lighting curve, homogeneous lighting throughout the projection area.<br>Average service life > 50.000 hours.<br>Low consumption and high efficiency.<br>Does not require maintenance.<br>Careful with the environment, it does not contain mercury. |





Detail without microperforated diffuser.

Brackets for plaster ceilings



Mounting



AVAILABLE



| CODE      | REFERENCE  | Kg.   | Light output<br>lm | Power<br>W | Efficiency<br>LED module +Driver<br>lm/W | DIMM<br>DALI | Emergency |      |
|-----------|--|-------|--------------------|------------|--|--------------|-----------|------|
|           |  |       |                    |            |  |              | MC-1      | MC-3 |
| LDC223K2B | LD-LED/C-25W 3800lm/840  | (5,0) | 3800               | 25         | 152                                      | ✓            | ✓         | ✓    |
| LDC224K4B | LD-LED/C-32W 4800lm/840  | (5,0) | 4800               | 32         | 150                                      | ✓            | ✓         | ✓    |
| LEKAL001  | ACC. RECESSED LD-LED/C   | -     | -                  | -          | -  | -            | -         | -    |
| 009230101 | BRACKETS FOR SMOOTH PLASTER CEILINGS<br>(UNDER REQUEST, 4 UNITS SET) | -     | -                  | -          | -  | -            | -         | -    |

Note: Only valid for modular ceilings 600X600mm.

Minimum order 10 units.

more information in [www.lux-may.com](http://www.lux-may.com)

LUX-MAY reserves the right to change product characteristics without notice.