



BULKHEADS IP65 • LED



BULKHEADS LED

- RD-1-PC-300
- RD-2-PC-300
- RD-3-PC-220
- RD-3-PC-296



RD-1-PC-300




RD-2-PC-300



RD-3-PC-296


RD-3-PC-220

Mounting	Surface.
Light source	LED modules SMD
Optical system	Opal diffuser and reflector lacquered in white.
Light distribution	Direct.
Wiring	Electronic control gear (EEI=A+). PF>0,95
Material	Body: ABS. Diffuser: Opaline polycarbonate.
Surface finish	Body: Grey colour.
Benefits	<p>LED luminaire with integrated electronic control gear. Technological guarantee. Optimal lighting curve, homogeneous throughout the projection area. Low power consumption and high efficiency. Average service life >30.000 hours. Maintenance-optimised design. Careful with the environment, does not contain mercury.</p>




RD-1-PC-300

Mounting




RD-2-PC-300

Mounting




RD-3-PC-220

Mounting



RD-3-PC-296

Mounting



CODE	REFERENCE	Kg.	Light output	Power	Efficiency	Colour temperature	Colour rendering index	Cooling
			lm	W	lm/W	CCT (K)	CRI (Ra)	
RD1121K2G	RD-1-PC-300-13W. 1200lm/4200K	(1,4)	1200	13	92	4200	>70	Passive
RD2121K2G	RD-2-PC-300-13W. 1200lm/4200K	(1,4)	1200	13	92	4200	>70	Passive
RD3121K1G	RD-3-PC-220-12W. 1100lm/4200K	(0,7)	1100	12	92	4200	>70	Passive
RD3221K8G	RD-3-PC-296-16W. 1800lm/4200K	(0,7)	1800	16	92	4200	>70	Passive