







WALL WASHER LED ECOCORNER





Mounting	Wall Washer.
Light source	LED LED
Optical system	Opal diffuser.
	Option 3000K and 6000K.
Light distribution	Direct/Indirect.
Wiring	Electronic control gear (EEI=A). PF>0,95
-	Possibility of incorporating dimmable electronic control gear (DALI)
	Possibility of incorporating diffinable electronic control gear (DALI)
Material	Body: Extruded aluminum. Diffuser: Opal.
Benefits	LED luminaire with integrated electronic control gear. Technological guarantee.
1500 125 80 Im/W	Optimal lighting curve, homogeneous illumination throughout the projection area. Low consumption and high efficiency. Average service life >50.000 hours. No maintenance required. Careful with the environment, does not contain mercury.
Surface finish	Body: White color RAL 9003. Under request, Grey RAL 9006 or Black RAL 9005.





220-240V 50-60Hz LED	ECG EEI=	F IP 40	min 8-20°C	max 35°C	AVAILABLE	ECG DALI

CODE	REFERENCE	Kg.	Light	Power	Efficiency	Colour	DIMM		
			output		LED module + Driver	temperature	DALI		
			lm	W	lm/W	CCT (K)			
ECR211K5B	ECOCORNER-12W 1500lm/840	(0,7)	1500	12	125	4000	✓		
Available colour temperature 3000K or 6000K.									