




WALL WASHER LED ECOSTAIR



Mounting	Wall Washer.
Light source	LED
Optical system	Opal diffuser. Option 3000K and 6000K.
Light distribution	Direct/Indirect.
Wiring	Electronic control gear (EEL=A). PF>0,95 Possibility of incorporating dimmable electronic control gear (DALI)
Material	Body: Extruded aluminum. Diffuser: Opal.
Benefits	LED luminaire with integrated electronic control gear. Technological guarantee. Optimal lighting curve, homogeneous illumination throughout the projection area. Low consumption and high efficiency. Average service life >50.000 hours. No maintenance required. Careful with the environment, does not contain mercury.
Surface finish	Body: White color RAL 9003. Under request, Grey RAL 9006 or Black RAL 9005.



Mounting



CODE	REFERENCE	Kg.	Light output lm	Power W	Efficiency LED module + Driver lm/W	Colour temperature CCT (K)	DIMM DALI
ESR212K2B	ECOSTAIR-570-26W 2200lm/840	(2,0)	2200	26	85	4000	✓
ESR313K3B	ECOSTAIR-850-39W 3300lm/840	(3,1)	3300	39	85	4000	✓
ESR414K4B	ECOSTAIR-1130-52W 4400lm/840	(3,9)	4400	52	85	4000	✓
ESR515K5B	ECOSTAIR-1410-65W 5500lm/840	(4,9)	5500	65	85	4000	✓
ESR616K6B	ECOSTAIR-1690-78W 6600lm/840	(5,8)	6600	78	85	4000	✓

Available colour temperature 3000K or 6000K.