




Lux-May

RECESSED IP65 • LED CLEAR ROOMS




IP65

RECESSED IP65 LED
P/OPALPC-IP65



P/OPALPC-IP65

TRIDONIC



Mounting	Recessed. Modular ceilings 600x600.
Light source	LED linear modules SMD OSRAM/TRIDONIC. 3000K y 4000K.
Optical system	Opal diffuser.
Light distribution	Direct.
Wiring	Electronic control gear (EEI=A++). PF>0,95 OSRAM/TRIDONIC/HELVAR. Possibility of incorporating dimmable electronic control gear(DALI) and/or emergency Kit (1 hour).
Material	Body: Galvanized steel lacquered in white with anti-corrosive treatment according to ENEC-10 and VDE standards. Diffuser: Opal. (Under request, microprismatic diffuser).
Surface finish	Body: Galvanized steel lacquered in white color RAL 9016. P/OPALPC-IP65 model, IP65 body.
Accessories	Available accessory for recess in plaster, plasterboard ... Available accessory for surface application.
Benefits	LED luminaire with integrated electronic control gear. Technological guarantee. Optimal lighting curve, homogeneous lighting throughout the projection area. Low consumption and high efficiency. Average service life >50.000 hours. Does not require maintenance. Careful with the environment, it does not contain mercury.

7600
lm

153
lm/W

>80
Ra




IP 67
Conector



Accessory
for surface.




Mounting RECESSED





Mounting SURFACE

P/OPALPC-IP65 (596x596)



P/OPALPC-IP65 (296x1196)



REFERENCE		Light output	Power	Efficiency	Colour temperature	Colour rendering index	DIMM DALI	Emergency MC-1
		lm	W	lm/W	CCT (K)	CRI (Ra)		
154234K9B	P/OPALPC-IP65 -32W 4900lm/840 (596x596)	4900	32	153	4000	>80	✓	✓
154235K8B	P/OPALPC-IP65 -42W 5800lm/840 (596x596)	5800	42	138	4000	>80	✓	✓
154237K6B	P/OPALPC-IP65 -55W 7600lm/840 (596x596)	7600	55	138	4000	>80	✓	✓
154334K9B	P/OPALPC-IP65 -32W 4900lm/840 (296x1196)	4900	32	153	4000	>80	✓	✓
154335K8B	P/OPALPC-IP65 -42W 5800lm/840 (296x1196)	5800	42	138	4000	>80	✓	✓
154337K6B	P/OPALPC-IP65 -55W 7600lm/840 (296x1196)	7600	55	138	4000	>80	✓	✓
LEKAL002	ACC. RECESSED P/OPALPC-IP65 600X600	-	-	-	-	-	-	-
1542200237	ACC. RECESSED P/OPALPC-IP65 1200x300	-	-	-	-	-	-	-
154331L001	ACC. SURFACE P/OPALPC-IP65 (596x596)	-	-	-	-	-	-	-
154334L001	ACC. SURFACE P/OPALPC-IP65 (296x1196)	-	-	-	-	-	-	-

Available colour temperature 3000K.

more information in www.lux-may.com

LUX-MAY reserves the right to change product characteristics without notice.