



RXR 90




RXC 90

ADJUSTABLE IN ONE DIRECTION


Mounting	Recessed.
Light source	SMD LED TRIDONIC.
Optical system	Reflector Aluminium lacquered. Standard 24°. Optional 16°, 36°. Colour temperature 4000K, standard. (Optional 3000K).
Light distribution	Direct.
Wiring	Electronic control gear (EEI=A+). PF>0,95 TRIDONIC. Possibility of incorporating dimmable electronic control gear (DALI) and/or emergency Kit (1 or 3 hours).
Material	Body: Aluminium lacquered. Reflector: Bright aluminum.
Surface finish	White RAL 9003 (standard). Optional grey RAL 9006, black RAL 9005.
Benefits	LED luminaire with integrated electronic control gear. Average service life > 50.000 hours. Colour rendering index Ra>80. Passive cooling. No UVA or infrared radiation. L80.B10. No maintenance required. Easy installation. Orientable in one way.




DIFERENTES COLORES
RAL DISPONIBLES



RXC 90



RXR 90



CODE	REFERENCE	Kg.	Light output lm	Power W	Efficiency LED module + Driver lm/W	Beam angle	DIMM DALI	Emergency	
								MC-1	MC-3
RXC102K0B	RXC-90-24°-13W 2000lm/840	(0,5)	2000	13	154	24°	✓	✓	
RXC103K0B	RXC-90-24°-19W 3000lm/840	(0,5)	3000	19	158	24°	✓	✓	
RXC104K3B	RXC-90-24°-26W 4300lm/840	(0,7)	4300	26	165	24°	✓	✓	
RXR102K0B	RXR-90-24°-13W 2000lm/840	(0,5)	2000	13	154	24°	✓	✓	
RXR103K0B	RXR-90-24°-19W 3000lm/840	(0,5)	3000	19	158	24°	✓	✓	
RXR104K3B	RXR-90-24°-26W 4300lm/840	(0,7)	4300	26	165	24°	✓	✓	

Under request, 3000K. Optional 16°, 36° optics.