



WATERPROOF FITTINGS • LED

IP-67 TUBULAR SLC

EFFICIENCY AT THE BEST PRICE




18W-36W-48W

HIGH EFFICIENCY

FAST CONNECTION

IP-67 TUBULAR-SLC



Mounting	Surface/ Suspended.
Light source	LED linear modules SMD
Optical system	Diffuser resistant to UVA rays. Colour temperature 4000K (standard). Under request: 3000K, 6000K.
Light distribution	Direct.
Wiring	Electronic control gear (EEI=A+) PF>0,95. Possibility of incorporating dimmable electronic control gear (DALI/1-10V).
Material	Body: Polycarbonate. Reflector: White Lacquered steel. Diffuser: Unbreakable longitudinal polycarbonate.
Surface finish	Body: White.
Accessories	Suspension set 2 uds. Under request: Connection of few luminaires between each other.
Benefits	Compact waterproof fitting. LED luminaire with integrated electronic control gear. Optimal lighting curve, homogeneous lighting. CRI (Ra) >80. Low power consumption and high efficiency. Maintenance-optimised design. Average service life > 30.000 hours. Careful with the environment, it does not contain mercury. Fast electrical connection without opening the luminaire.



ACCESSORIES INCLUDED

Fast connector



Safely connection or disconnection




Brackets for surface mounting



Suspended mounting



Surface mounting



SIZE mm	D1	D2	L
TUBULAR-S	66	60	672
TUBULAR-M	66	60	1252
TUBULAR-L	66	60	1543



CODE	REFERENCE	Light	Power	Efficiency	Colour	DIMM		Emergency		Size
		Output	W	LED + Driver	temperature	DALI	1-10V	MC-1	MC-3	
TOL212K2G	TUBULAR/SLC-S-IP67-18W 2200lm/840	2200	18	122	4000	✓	✓	✓	-	662
TOL314K2G	TUBULAR/SLC-M-IP67-36W 4200lm/840	4200	36	117	4000	✓	✓	✓	✓	1242
TOL415K7G	TUBULAR/SLC-L-IP67-48W 5700lm/840	5700	48	119	4000	✓	✓	✓	✓	1533
15620002	ACC. SUSPENSION SET (2 PIECES)	-	-	-	-	-	-	-	-	-
1563610L001	INC.ELEC LC EST/ONIX SLC/HF ✓ Under request	-	-	-	-	-	-	-	-	-