



# WATERPROOF FITTINGS • LED

## TRIDONIC IP-67 TUBULAR

### HIGH EFFICIENCY lm/w




16W-17W-33W-34W-41W-42W

HIGH EFFICIENCY

FAST CONNECTION

#### IP-67 TUBULAR



<b>Mounting</b>	Surface/ Suspended.
<b>Light source</b>	LED linear modules SMD
<b>Optical system</b>	Diffuser resistant to UVA rays. Colour temperature 4000K (standard). Under request: 3000K, 6000K.
<b>Light distribution</b>	Direct.
<b>Wiring</b>	Electronic control gear (EEL=A+) PF>0,95. Possibility of incorporating dimmable electronic control gear (DALI/1-10V).
<b>Material</b>	Body: Polycarbonate. Reflector: White Lacquered steel. Diffuser: Unbreakable longitudinal polycarbonate.
<b>Surface finish</b>	Body: White.
<b>Accessories</b>	Suspension set 2 uds.  Under request: Connection of few luminaires between each other.
<b>Benefits</b>	Compact waterproof fitting. LED luminaire with integrated electronic control gear. Optimal lighting curve, homogeneous lighting. CRI (Ra) >80. Low power consumption and high efficiency. Maintenance-optimised design. Average service life > 30.000 hours. Careful with the environment, it does not contain mercury. <b>Fast electrical connection without opening the luminaire.</b>



#### ACCESSORIES INCLUDED

##### Fast connector



Safely connection or disconnection




Brackets for surface mounting



##### Suspended mounting



##### Surface mounting



SIZE mm	D1	D2	L
TUBULAR-S	66	60	672
TUBULAR-M	66	60	1252
TUBULAR-L	66	60	1543



CODE	REFERENCE	Light Output	Power	Efficiency	Colour temperature	DIMM		Emergency		Size mm
						DALI	1-10V	MC-1	MC-3	
TOL212K4G	TUBULAR-S-IP67-17W 2400Lm/840 TR	2400	17	141	4000	✓	✓	✓	-	662
TOL314K8G	TUBULAR-M-IP67-34W 4800Lm/840 TR	4800	34	141	4000	✓	✓	✓	✓	1242
TOL416K0G	TUBULAR-L-IP67-42W 6000Lm/840 TR	6000	42	143	4000	✓	✓	✓	✓	1533
TOL213K2G	TUBULAR-S-IP67-16W 3200Lm/840 TR	3200	16	200	4000	✓	✓	✓	-	662
TOL416K4G	TUBULAR-M-IP67-33W 6400Lm/840 TR	6400	33	194	4000	✓	✓	✓	✓	1242
TOL428K0G	TUBULAR-L-IP67-41W 8000Lm/840 TR	8000	41	195	4000	✓	✓	✓	✓	1533
15620002	ACC. SUSPENSION SET (2 PIECES)	-	-	-	-	-	-	-	-	-
1563610L001	INC.ELEC LC EST/ONIX SLC/HF	-	-	-	-	-	-	-	-	-
✓ Under request										