





# RECESSED INDIRECT • LED POLYVALENT

RECESSED INDIRECT LED  
MICROPERFORATED  
LD-LED/C



LD-LED/C



Microperforated

<b>Mounting</b>	Recessed. Armstrong ceilings, plaster, plasterboard.
<b>Light source</b>	LED  OSRAM/TRIDONIC. Colour temperature 4000K. Under request, 3000K.
<b>Optical system</b>	Diffuser.
<b>Light distribution</b>	Indirect.
<b>Wiring</b>	Electronic control gear (EEI=A+). PF>0,95 OSRAM/TRIDONIC/HELVAR. Possibility of incorporating dimmable electronic control gear (DALI) and/or emergency Kit (1 or 3 hours).
<b>Material</b>	Body: White enameled steel. High torsional strength and guaranteed minimum thickness of 0.6mm, according to ENEC-10 and VDE standards. Diffuser: Microperforated. Simple assembly and easy installation, for its quick accessibility to the connection terminal.
<b>Surface finish</b>	Body: Epoxy-polyester in white opaque and satin antiglare. Stable to ultraviolet and anti-yellowing radiations.
<b>Benefits</b>	LED luminaire with integrated electronic control gear. Technological guarantee. Optimal lighting curve, homogeneous lighting throughout the projection area. Average service life > 50.000 hours. Low consumption and high efficiency. Does not require maintenance. Careful with the environment, it does not contain mercury.

4400  
lm

100  
lm/W




>80  
Ra



Brackets for plaster ceilings



Mounting



CODE	REFERENCE	Kg.	Light output lm	Power W	Efficiency LED module +Driver lm/W	DIMM DALI	Emergency	
							MC-1	MC-3
LDC223K2B	LD-LED/C-32W 3200lm/840	(5,0)	3200	32	100	✓	✓	✓
LDC224K4B	LD-LED/C-50W 4400lm/840	(5,0)	4400	50	88	✓	✓	✓
LEKAL001	ACC. RECESSED LD-LED/C	-	-	-	-	-	-	-
009230101	BRACKETS FOR SMOOTH PLASTER CEILINGS (UNDER REQUEST, 4 UNITS SET)	-	-	-	-	-	-	-

Note: Only valid for modular ceilings 600X600mm.  
Minimum order 10 units.

more information in [www.lux-may.com](http://www.lux-may.com)

LUX-MAY reserves the right to change product characteristics without notice.